

## § 55.219

lighter core loads should be rated proportionately.

[T.D. ATF-87, 46 FR 40384, Aug. 7, 1981, as amended by T.D. ATF-400, 63 FR 45003, Aug. 24, 1998]

### § 55.219 Table of distances for storage of low explosives.

Pounds		From inhabited building distance (feet)	From public railroad and highway distance (feet)	From above ground magazine (feet)
Over	Not over			
0	1,000	75	75	50
1,000	5,000	115	115	75
5,000	10,000	150	150	100
10,000	20,000	190	190	125
20,000	30,000	215	215	145
30,000	40,000	235	235	155
40,000	50,000	250	250	165
50,000	60,000	260	260	175
60,000	70,000	270	270	185
70,000	80,000	280	280	190
80,000	90,000	295	295	195
90,000	100,000	300	300	200
100,000	200,000	375	375	250
200,000	300,000	450	450	300

### § 55.220 Table of separation distances of ammonium nitrate and blasting agents from explosives or blasting agents.

TABLE: DEPARTMENT OF DEFENSE AMMUNITION AND EXPLOSIVES STANDARDS, TABLE 5-4.1 EXTRACT; 4145.27 M, MARCH 1969

Donor weight (pounds)		Minimum separation distance of acceptor from donor when barricaded (ft.)		Minimum thickness of artificial barricades (in.)
Over	Not over	Ammonium nitrate	Blasting agent	
.....	100	3	11	12
100	300	4	14	12
300	600	5	18	12
600	1,000	6	22	12
1,000	1,600	7	25	12
1,600	2,000	8	29	12
2,000	3,000	9	32	15
3,000	4,000	10	36	15
4,000	6,000	11	40	15
6,000	8,000	12	43	20
8,000	10,000	13	47	20
10,000	12,000	14	50	20
12,000	16,000	15	54	25
16,000	20,000	16	58	25
20,000	25,000	18	65	25
25,000	30,000	19	68	30
30,000	35,000	20	72	30
35,000	40,000	21	76	30
40,000	45,000	22	79	35
45,000	50,000	23	83	35
50,000	55,000	24	86	35
55,000	60,000	25	90	35
60,000	70,000	26	94	40
70,000	80,000	28	101	40
80,000	90,000	30	108	40
90,000	100,000	32	115	40

## 27 CFR Ch. I (4-1-00 Edition)

Donor weight (pounds)		Minimum separation distance of acceptor from donor when barricaded (ft.)		Minimum thickness of artificial barricades (in.)
Over	Not over	Ammonium nitrate	Blasting agent	
100,000	120,000	34	122	50
120,000	140,000	37	133	50
140,000	160,000	40	144	50
160,000	180,000	44	158	50
180,000	200,000	48	173	50
200,000	220,000	52	187	60
220,000	250,000	56	202	60
250,000	275,000	60	216	60
275,000	300,000	64	230	60

TABLE: NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) OFFICIAL STANDARD NO. 492, 1968

### Notes of Table of Separation Distances of Ammonium Nitrate and Blasting Agents From Explosives or Blasting Agents

(1) This table specifies separation distances to prevent explosion of ammonium nitrate and ammonium nitrate-based blasting agents by propagation from nearby stores of high explosives or blasting agents referred to in the table as the "donor." Ammonium nitrate, by itself, is not considered to be a donor when applying this table. Ammonium nitrate, ammonium nitrate-fuel oil or combinations thereof are acceptors. If stores of ammonium nitrate are located within the sympathetic detonation distance of explosives or blasting agents, one-half the mass of the ammonium nitrate is to be included in the mass of the donor.

(2) When the ammonium nitrate and/or blasting agent is not barricaded, the distances shown in the table must be multiplied by six. These distances allow for the possibility of high velocity metal fragments from mixers, hoppers, truck bodies, sheet metal structures, metal containers, and the like which may enclose the "donor." Where explosives storage is in bullet-resistant magazines or where the storage is protected by a bullet-resistant wall, distances and barricade thicknesses in excess of those prescribed in the table in § 55.218 are not required.

(3) These distances apply to ammonium nitrate that passes the insensitivity test prescribed in the definition of ammonium nitrate fertilizer issued by the Fertilizer Institute.<sup>1</sup> Ammonium nitrate failing to pass the test must be stored at separation distances in accordance with the table in § 55.218.

(4) These distances apply to blasting agents which pass the insensitivity test prescribed in regulations of the U.S. Department of Transportation (49 CFR part 173).

<sup>1</sup>Definition and Test Procedures for Ammonium Nitrate Fertilizer, Fertilizer Institute 1015-18th St. N.W. Washington, DC 20036.

(5) Earth or sand dikes, or enclosures filled with the prescribed minimum thickness of earth or sand are acceptable artificial barricades. Natural barricades, such as hills or timber of sufficient density that the surrounding exposures which require protection cannot be seen from the "donor" when the trees are bare of leaves, are also acceptable.

(6) For determining the distances to be maintained from inhabited buildings, passenger railways, and public highways, use the table in § 55.218.

**§ 55.221 Requirements for display fireworks, pyrotechnic compositions, and explosive materials used in assembling fireworks or articles pyrotechnic.**

(a) Display fireworks, pyrotechnic compositions, and explosive materials used to assemble fireworks and articles pyrotechnic shall be stored at all times as required by this Subpart unless they are in the process of manufacture, assembly, packaging, or are being transported.

(b) No more than 500 pounds (227 kg) of pyrotechnic compositions or explosive materials are permitted at one time in any fireworks mixing building, any building or area in which the pyrotechnic compositions or explosive materials are pressed or otherwise prepared for finishing or assembly, or any finishing or assembly building. All pyrotechnic compositions or explosive materials not in immediate use will be stored in covered, non-ferrous containers.

(c) The maximum quantity of flash powder permitted in any fireworks process building is 10 pounds (4.5 kg).

(d) All dry explosive powders and mixtures, partially assembled display fireworks, and finished display fireworks shall be removed from fireworks process buildings at the conclusion of a day's operations and placed in approved magazines.

[T.D. ATF-293, 55 FR 3722, Feb. 5, 1990, as amended by T.D. ATF-400, 63 FR 45004, Aug. 24, 1998]

**§ 55.222 Table of distances between fireworks process buildings and between fireworks process and fireworks nonprocess buildings.**

Net weight of fireworks <sup>1</sup> (pounds)	Display fireworks <sup>2</sup> (feet)	Consumer fireworks <sup>3</sup> (feet)
0-100 .....	57 .....	37

Net weight of fireworks <sup>1</sup> (pounds)	Display fireworks <sup>2</sup> (feet)	Consumer fireworks <sup>3</sup> (feet)
101-200 .....	69 .....	37
201-300 .....	77 .....	37
301-400 .....	85 .....	37
401-500 .....	91 .....	37
Above 500 .....	Not permitted <sup>4,5</sup> .....	Not permitted <sup>4,5</sup>

<sup>1</sup>Net weight is the weight of all pyrotechnic compositions, and explosive materials and fuse only.

<sup>2</sup>The distances in this column apply only with natural or artificial barricades. If such barricades are not used, the distances must be doubled.

<sup>3</sup>While consumer fireworks or articles pyrotechnic in a finished state are not subject to regulation, explosive materials used to manufacture or assemble such fireworks or articles are subject to regulation. Thus, fireworks process buildings where consumer fireworks or articles pyrotechnic are being processed shall meet these requirements.

<sup>4</sup>A maximum of 500 pounds of in-process pyrotechnic compositions, either loose or in partially-assembled fireworks, is permitted in any fireworks process building. Finished display fireworks may not be stored in a fireworks process building.

<sup>5</sup>A maximum of 10 pounds of flash powder, either in loose form or in assembled units, is permitted in any fireworks process building. Quantities in excess of 10 pounds must be kept in an approved magazine.

[T.D. ATF-293, 55 FR 3723, Feb. 5, 1990, as amended by T.D. ATF-400, 63 FR 45004, Aug. 24, 1998]

**§ 55.223 Table of distances between fireworks process buildings and other specified areas.**

DISTANCE FROM PASSENGER RAILWAYS, PUBLIC HIGHWAYS, FIREWORKS PLANT BUILDINGS USED TO STORE CONSUMER FIREWORKS AND ARTICLES PYROTECHNIC, MAGAZINES AND FIREWORKS SHIPPING BUILDINGS, AND INHABITED BUILDINGS.<sup>3,4,5</sup>

Net weight of fireworks <sup>1</sup> (pounds)	Display fireworks <sup>1</sup> (feet)	Consumer fireworks <sup>2</sup> (feet)
0-100 .....	200 .....	25
101-200 .....	200 .....	50
201-300 .....	200 .....	50
301-400 .....	200 .....	50
401-500 .....	200 .....	50
Above 500 .....	Not permitted .....	Not permitted.

<sup>1</sup>Net weight is the weight of all pyrotechnic compositions, and explosive materials and fuse only.

<sup>2</sup>While consumer fireworks or articles pyrotechnic in a finished state are not subject to regulation, explosive materials used to manufacture or assemble such fireworks or articles are subject to regulation. Thus, fireworks process buildings where consumer fireworks or articles pyrotechnic are being processed shall meet these requirements.

<sup>3</sup>This table does not apply to the separation distances between fireworks process buildings (see § 55.222) and between magazines (see §§ 55.218 and 55.224).

<sup>4</sup>The distances in this table apply with or without artificial or natural barricades or screen barricades. However, the use of barricades is highly recommended.

<sup>5</sup>No work of any kind, except to place or move items other than explosive materials from storage, shall be conducted in any building designated as a warehouse. A fireworks plant warehouse is not subject to § 55.222 or this section, tables of distances.

[T.D. ATF-293, 55 FR 3723, Feb. 5, 1990, as amended by T.D. ATF-400, 63 FR 45004, Aug. 24, 1998]